



Technical Details

Barrel length; **6"** / 152,4 mm, **8"** / 203,2 mm **12"** / 300,5 mm, **16"** / 406,5 mm

Barrel Twist; **1:8**

Caliber; **9x19** NATO

Overall Length (min/max); 720 / 810 mm (**28.3"** / **31.8"**)

Weight (w/o optics); **88.1 oz** – 2500 gr

Stock type; Adjustable, with 7 positions

Handguard; Free floating MIL-STD

M1913 Picatinny Accessory Ray

Operation; Blowback, Closed bolt

Forward Assist; No

Trigger Weight; **1.5 kg** – **2.2 kg**

Magazine Type; Glock **17** round

STD/**33** round optiona

Fire Selector; Safe, Semi-Automatic, Full-Automatic

Sling Attachment Points; QD on both sides of the stock

Muzzle Velocity (approx. with M855 ammunition); **420** m/s

Rate of Fire; Approximately 900-1000 RPM

Accuracy; 2 MOA @ 25m, 3 MOA @ 50m,

5 MOA @ 100m, 15 MOA @ 300m

Barrel Life; **20 000** rounds minimum

Parts Life; **15 000** rounds minimum

Other; Stainless steel small parts,

improved low mass bolt, long-life springs

Silencer; Optional



9x19 mm Silencer, Flash Hider



Black

Prod. Code
UT9S-SLN9S-B



Utas Flash Hider;
9x19 mm (Thread M15X1)

Technical Details

Product Code; UT9S-SLN9S

Caliber; 9 x 19 NATO

Overall Length; 103 mm

Diameter; 53 mm

Weight; 464 gr. Without flash hider installed

Build Material; Stainless steel baffles and 4140 steel body

Color; Black, OD Green, Flat Dark Earth

Finish; Cerakote

Flash Hider; Included M15X1

Full-Auto Rated; Full-Auto Rated

Wrench; Included

Prod. Code
8033-BBL-919



OD Green

Prod. Code
UT9S-SLN9S-ODG

